



# GBC Catena 105

1715850

## Product Description

Thermal and Pressure Sensitive Film laminator up to 40". Versatile 40" freestanding lamination, encapsulation and mounting of digital inkjet output using thermal films or pressure sensitive (PSA) films.

## Each information

|               |              |
|---------------|--------------|
| Depth         | 0            |
| Width         | 0            |
| Height        | 0            |
| Gross weight  | 155.00lbs    |
| UPC#          | 033816064690 |
| Unit quantity | 1            |

## Case information

|               |              |
|---------------|--------------|
| Depth         | 0            |
| Width         | 0            |
| Height        | 0            |
| Gross weight  | 155.00lbs    |
| UPC#          | 033816064690 |
| Unit quantity | 1            |

## Shipping Information

|                        |      |
|------------------------|------|
| Country of origin      | KR   |
| Minimum Order Quantity | 1    |
| Lowest possible unit   | Each |

## General information

|       |          |
|-------|----------|
| Color | 230 VOLT |
|-------|----------|

## Features

- Infrared heat detection provides instant reaction to heat changes on the silicone rollers
- Mounting on boards up to 3/16" thick
- Rewind to accommodate PSA release liner
- Silicone heat rollers for quality seal without scratching
- Speed: 1.5 fpm-5 fpm (45.7cm-152cm)
- Max. Roll OD 5"

## Specifications

- Core Diameter 1" and 2.25"

## Other information

- Finish Gloss and Matte