



SPIRE III 64T – 64” Thermal Wide Format Laminator

SPIRE

1737175



Product Description

Running at a maximum speed of 20 feet per minute with 4" heat rollers, the SPIRE III 64T machines is fast and retain heat better for longer runs. Even beginners will find the SPIRE III easy-to-use with a user-friendly control panel and auto grip, easy-load supply shafts for no-hassle film loading. Designed with an eye for increasing versatility, a 2" mounting gap allows for mounting of thicker substrates while optional unwinds and rewinds and roll-to-roll capabilities can be easily added later.

Features

- Simple, intuitive control panel with LED pressure readout
- Hand crank for opening and closing rollers provides an infinite choice of settings
- Deep feed table makes feeding larger sheets effortless
- 20 feet per minute laminating capability
- Foot pedal for hands-free operation
- Up to 64" wide laminating and mounting capabilities
- Independently controlled upper and lower heat rollers allow for running multiple thermal film gauges and PSA films concurrently

Specifications

- **Warranty Group** N/A

Retail Packaging Information

| | |
|---------------|--------------|
| Depth | 32.1" |
| Width | 81.9" |
| Height | 62.2" |
| Gross weight | 1166.00lbs |
| UPC# | 033816501362 |
| Unit quantity | 1 |

Master Case Information

| | |
|---------------|--------------|
| Depth | 32.1" |
| Width | 81.9" |
| Height | 62.2" |
| Gross weight | 1166.00lbs |
| UPC# | 033816501362 |
| Unit quantity | 1 |

Shipping Information

| | |
|------------------------|---|
| Minimum Order Quantity | 1 |
|------------------------|---|

